



Raccord démontable pour maintenance.

Dismantled connection for maintenace

Construction: Tout acier inox

Built in stainless steel

Fluide standard: Azote

Standard fluid: Nitrogen

Raccordements:

Connections:

Côté flexible, mâle 1/4 NPT, serrage six pans de 14.

- Fhose pipe connexion: 1/4 NPT male, 14 mm six sided screwwing

- Côté process, femelle Nato tournant avec joint nylon, serrage: six pans de 12.

- For process connexion, turning female nato with nylon joint: 12mm six sided screwing

Pression maxi: 400 bar / 5800 psi

Maxi pressure: 400 bar / 5800 psi

Dimensions:

Dimensions:

-longueur hors tout: 42 mm

-Maxi lenght: 42 mm

-Diamètre hors tout: 18 mm

-Maxi diameter: 18 mm

Poids: 0,051 kg

Weight: 0,051 Kg

Pièces détachées disponible

Spare parts on request



LJP Industries
18, rue de la place
77410 CLAYE - SOUILLY CEDEX
Tel: 01.60.26.16.72
Contact: infos@ljpairo.com

**RACCORD
NATO FEMELLE TOURNANT / 1/4 NPT MALE
CONNECTION
FEMALE NATO TURNING - MALE 1/4 NPT**

Creation date :
2009/09/14

P/N : LJNA 3047

Sheet
1/1